



CHARGING CAPS

ACCESSORIES



HAT
COLLECTIVE™
HUMAN ACTIVE TECHNOLOGY


GET THE MOST OUT OF YOUR WORKSPACE.

Complete your workspace with the addition of power solutions.



CHARGING CAP FOR SINGLE TOP DOWN MOUNT

Finishes



Features

- Dual USB-A charger ports
- Single USB-C charger port
- Input: 100-240VAC, 50/60Hz, 2.0A (Max)
- Output: 24VDC, 3A, 72w
- Mount: Snaps onto mount
- Compatibility: Single top down mount

Specifications

- Input:
100-240VAC; Frequency: 50/60Hz;
Current: 15A Max.
- Output:
1x USB-C: 5V3A, 9V3A, 12V3A, 15V3A, 20V3A, PD3.0 Compatible, 65W Max.
- 2x USB-A: 5V3A, 9V2A, 12V1.5A, QC 3.0 Compatible, 18W max
- Both USB-A Ports in Use: QC 3.0 Compatible (18W Max)
- 1x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V3A, 9V2A, 12V1.5A, (18W Max)
- 2x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V2A (10W Max) each.


Part Numbers

CHG-CAP-1-AU-__



CHARGING CAP FOR DUAL E2 MOUNT

Finishes



Features

- Dual USB-A charger ports
- Single USB-C charger port
- Input: 100-240VAC, 50/60Hz, 2.0A (Max)
- Output: 24VDC, 3A, 72w
- Mount: Snaps onto mount
- Compatibility: Dual E2 top down mount

Specifications

- Input:
100-240VAC; Frequency: 50/60Hz;
Current: 15A Max.
- Output:
1x USB-C: 5V3A, 9V3A, 12V3A, 15V3A, 20V3A, PD3.0 Compatible, 65W Max.
- 2x USB-A: 5V3A, 9V2A, 12V1.5A, QC 3.0 Compatible, 18W max
- Both USB-A Ports in Use: QC 3.0 Compatible (18W Max)
- 1x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V3A, 9V2A, 12V1.5A, (18W Max)
- 2x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V2A (10W Max) each.

Part Numbers

CHG-CAP-E-AU-__