



CHARGING CAPS

ACCESSORIES



HAT
COLLECTIVE™
HUMAN ACTIVE TECHNOLOGY

GET THE MOST OUT OF YOUR WORKSPACE.

Complete your workspace with the addition of power solutions.



CHARGING CAP FOR SINGLE TOP DOWN MOUNT

Finishes

- White WH
- Silver SI
- Black BK

Features

Dual USB-A charger ports
Single USB-C charger port
Input: 100-240VAC, 50/60Hz, 2.0A (Max)
Output: 24VDC, 3A, 72w
Mount: Snaps onto mount
Compatibility: Single top down mount

Specifications

Input:
100-240VAC; Frequency: 50/60Hz;
Current: 15A Max.

Output:
1x USB-C: 5V3A, 9V3A, 12V3A, 15V3A, 20V3A, PD3.0 Compatible, 65W Max.

2x USB-A: 5V3A, 9V2A, 12V1.5A, QC 3.0 Compatible, 18W max

Both USB-A Ports in Use: QC 3.0 Compatible (18W Max)

1x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V3A, 9V2A, 12V1.5A, (18W Max)

2x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V2A (10W Max) each.

Part Numbers

CHG-CAP-1-__



CHARGING CAP FOR DUAL TOP DOWN MOUNT

Finishes

- White WH
- Silver SI
- Black BK

Features

Dual USB-A charger ports
Single USB-C charger port
Input: 100-240VAC, 50/60Hz, 2.0A (Max)
Output: 24VDC, 3A, 72w
Mount: Snaps onto mount
Compatibility: Dual top down mount

Specifications

Input:
100-240VAC; Frequency: 50/60Hz;
Current: 15A Max.

Output:
1x USB-C: 5V3A, 9V3A, 12V3A, 15V3A, 20V3A, PD3.0 Compatible, 65W Max.

2x USB-A: 5V3A, 9V2A, 12V1.5A, QC 3.0 Compatible, 18W max

Both USB-A Ports in Use: QC 3.0 Compatible (18W Max)

1x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V3A, 9V2A, 12V1.5A, (18W Max)

2x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V2A (10W Max) each.

Part Numbers

CHG-CAP-2-__



CHARGING CAP FOR DUAL E2 MOUNT

Finishes

- White WH
- Silver SI
- Black BK

Features

Dual USB-A charger ports
Single USB-C charger port
Input: 100-240VAC, 50/60Hz, 2.0A (Max)
Output: 24VDC, 3A, 72w
Mount: Snaps onto mount
Compatibility: Dual E2 top down mount

Specifications

Input:
100-240VAC; Frequency: 50/60Hz;
Current: 15A Max.

Output:
1x USB-C: 5V3A, 9V3A, 12V3A, 15V3A, 20V3A, PD3.0 Compatible, 65W Max.

2x USB-A: 5V3A, 9V2A, 12V1.5A, QC 3.0 Compatible, 18W max

Both USB-A Ports in Use: QC 3.0 Compatible (18W Max)

1x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V3A, 9V2A, 12V1.5A, (18W Max)

2x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V2A (10W Max) each.

Part Numbers

CHG-CAP-E-__