



# CHARGING CAPS

ACCESSORIES



HAT  
DESIGN WORKS™  
HUMAN ACTIVE TECHNOLOGY

# GET THE MOST OUT OF YOUR WORKSPACE.

Complete your workspace with the addition of power solutions.



## CHARGING CAP FOR SINGLE TOP DOWN MOUNT

### Finishes

- White WH
- Silver SI
- Black BK

### Features

Dual USB-A charger ports  
Single USB-C charger port  
Input: 100-240VAC, 50/60Hz, 2.0A (Max)  
Output: 24VDC, 3A, 72w  
Mount: Snaps onto mount  
Compatibility: Single top down mount

### Specifications

Input:  
100-240VAC; Frequency: 50/60Hz;  
Current: 15A Max.

Output:  
1x USB-C: 5V3A, 9V3A, 12V3A, 15V3A, 20V3A, PD3.0 Compatible, 65W Max.  
2x USB-A: 5V3A, 9V2A, 12V1.5A, QC 3.0 Compatible, 18W max  
Both USB-A Ports in Use: QC 3.0 Compatible (18W Max)  
1x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V3A, 9V2A, 12V1.5A, (18W Max)  
2x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V2A (10W Max) each.

### Part Numbers

CHG-CAP-1-\_\_

## CHARGING CAP FOR DUAL TOP DOWN MOUNT

### Finishes

- White WH
- Silver SI
- Black BK

### Features

Dual USB-A charger ports  
Single USB-C charger port  
Input: 100-240VAC, 50/60Hz, 2.0A (Max)  
Output: 24VDC, 3A, 72w  
Mount: Snaps onto mount  
Compatibility: Single top down mount

### Specifications

Input:  
100-240VAC; Frequency: 50/60Hz;  
Current: 15A Max.

Output:  
1x USB-C: 5V3A, 9V3A, 12V3A, 15V3A, 20V3A, PD3.0 Compatible, 65W Max.  
2x USB-A: 5V3A, 9V2A, 12V1.5A, QC 3.0 Compatible, 18W max  
Both USB-A Ports in Use: QC 3.0 Compatible (18W Max)  
1x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V3A, 9V2A, 12V1.5A, (18W Max)  
2x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V2A (10W Max) each.

### Part Numbers

CHG-CAP-2-\_\_

## CHARGING CAP FOR DUAL E2 MOUNT

### Finishes

- White WH
- Silver SI
- Black BK

### Features

Dual USB-A charger ports  
Single USB-C charger port  
Input: 100-240VAC, 50/60Hz, 2.0A (Max)  
Output: 24VDC, 3A, 72w  
Mount: Snaps onto mount  
Compatibility: Single top down mount

### Specifications

Input:  
100-240VAC; Frequency: 50/60Hz;  
Current: 15A Max.

Output:  
1x USB-C: 5V3A, 9V3A, 12V3A, 15V3A, 20V3A, PD3.0 Compatible, 65W Max.  
2x USB-A: 5V3A, 9V2A, 12V1.5A, QC 3.0 Compatible, 18W max  
Both USB-A Ports in Use: QC 3.0 Compatible (18W Max)  
1x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V3A, 9V2A, 12V1.5A, (18W Max)  
2x USB-A and 1x USB-C Ports in Use: USB-C 5V3A, 9V3A, 12V3A, 15V3A (45W Max); USB-A 5V2A (10W Max) each.

### Part Numbers

CHG-CAP-E-\_\_