



# POWER

ACCESSORIES



HAT  
COLLECTIVE™  
HUMAN ACTIVE TECHNOLOGY

# GET THE MOST OUT OF YOUR WORKSPACE.

Complete your workspace with the addition of power solutions.



**SMPM-3AA-C**  
SURFACE MOUNTED POWER/DATA MODULE

**Finishes**

- White  
WH
- Black  
BK

**Features**

- Dual power receptacles
- Dual USB-A charger ports
- Mount: Clamp
- Compatibility: Desk edge .75" - 1.375"

**Specifications**

Input:  
90-240VAC; Frequency: 50/60Hz;  
Current: 15A max

Output:  
2 x AC: 110VAC, 15A Max  
2x USB-A: 5V2.4A, 12W Max

**Part Numbers**

SMPM-3AA-C-\_\_



**SMPM-3AC-C**  
SURFACE MOUNTED POWER/DATA MODULE

**Finishes**

- White  
WH
- Black  
BK

**Features**

- Dual power receptacles
- Single USB-A charger port
- Single USB-C charger port
- Mount: Clamp
- Compatibility: Desk edge .75" - 1.375"

**Specifications**

Input:  
90-240VAC; Frequency: 50/60Hz;  
Current: 15A max

Output:  
2x AC Adaptors: 110VAC, 15A Max  
Single ports in use:  
USB-C: 20V1.25A, 15V1.4A, 9V2.2A,  
5V3A, 25W Max., PD3.0  
USB-A: 5V3A, 9V2A, 12V1.5A, 18W  
Max, QC3.0/2.0  
Both ports in use:  
USB-C 5V2A (10W Max)  
USB-A 5V2A (10W Max)


**Part Numbers**

SMPM-3AC-C-\_\_



**SMPM-5-AAC-WRLS  
SURFACE MOUNTED POWER/DATA MODULE**

**Finishes**



**Features**

Dual power receptacles  
 Dual USB-A charger ports  
 Single USB-C charger port  
 Wireless charging capabilities  
 Mount: Clamp  
 Compatibility: Desk edge .75" - 1.375"

**Specifications**

Input:  
 90-240VAC; Frequency: 50/60Hz;  
 Current: 15A max


Output:  
 2x AC Adaptors: 110VAC, 15A Max  
 1x USB-C: 5V/3A, 9V/3A, 12V/3A,  
 15V/3A, 20V/3.25A, PD3.0,  
 APPLE2.4A, DCP1.5A, QC2.0/3.0, AFC,  
 PPS compatible, 65W Max.  
 2x USB-A: 5V3A, 9V2A, 12V1.5A,  
 QC2.0 & QC3.0, PPS compatible, 18W  
 Max.  
 1x USB-A and 1x USB-C Ports in Use:  
 USB-C 5V3A, 9V3A, 12V3A, 15V2.67A,  
 20V2.25A (45W Max); USB-A 5V3A,  
 9V2A, 12V1.5A (18W Max)  
 1x USB-C and 2x USB-A Ports in Use:  
 USB-C 5V3A, 9V3A, 12V3A, 15V2.67A,  
 20V2.25A (45W Max); USB-A 5V3A  
 (15W Max) each.

**Part Numbers**

SMPM-5-AAC-WRLS-\_\_




CHG-CAP-1



CHG-CAP-E

**CHG-CAP-1 | CHG-CAP-E  
SNAP ON CHARGING MOUNT**

**Finishes**



**Features**

Dual USB-A charger ports  
 Single USB-C charger port  
 Input: 100-240VAC, 50/60Hz, 2.0A (Max)  
 Output: 24VDC, 3A, 72w  
 Mount: Snaps onto mount  
 Compatibility: Single top down mount

**Specifications**

Input:  
 100-240VAC; Frequency: 50/60Hz;  
 Current: 15A Max.

Output:  
 1x USB-C: 5V3A, 9V3A, 12V3A, 15V3A,  
 20V3A, PD3.0 Compatible, 65W Max.  
 2x USB-A: 5V3A, 9V2A, 12V1.5A, QC  
 3.0 Compatible, 18W max  
 Both USB-A Ports in Use: QC 3.0  
 Compatible (18W Max)  
 1x USB-A and 1x USB-C Ports in Use:  
 USB-C 5V3A, 9V3A, 12V3A, 15V3A  
 (45W Max); USB-A 5V3A, 9V2A,  
 12V1.5A, (18W Max)  
 2x USB-A and 1x USB-C Ports in Use:  
 USB-C 5V3A, 9V3A, 12V3A, 15V3A  
 (45W Max); USB-A 5V2A (10W Max)  
 each.

**Part Numbers**

CHG-CAP-1-\_\_ (top down mount)  
 CHG-CAP-E-\_\_ (dual E2)