



REYA POWER

ACCESSORIES



HAT
COLLECTIVE™
HUMAN ACTIVE TECHNOLOGY


SMART. BEAUTIFUL. POWERFUL.

Meet Reya – our new power family. Reya’s design-forward architecture with soft, curved lines offers a full spectrum of mountable power options for your workstation. Whatever your power needs, big or small, Reya provides power conveniently at your fingertips.



LOW PROFILE USB HUB*

Finishes



Features

- 1 USB-A charger port
- 1 USB-C charger port
- Can charge laptop up to 65 Watts
- Mount: Desk edge/surface mount, under mount, edge mount (Desk edge/surface mount: 0.5" - 1.75")

Specifications

Input: DC, 65W max from HAT Base Control Box
 Output:
 Single Port In Use:
 USB-C: QC2.0, QC3.0, PD3.0, PPS, 65W max
 USB-A: 5V/2A, 10W max
 Both Ports In Use:
 USB-C: 20V2.25A max
 USB-A: 5V2A max

Dimensions

Product: 2.4" x 2.2" x 1.2"
 Cord Length: 5'

Part Numbers


PWR-AC-__

* Compatible with HAT bases only



STANDARD SURFACE POWER MODULE

Finishes



Features

- 2 power receptacles
- 1 USB-A charger port
- 2 USB-C charger ports
- Can charge laptop up to 65 Watts
- Mount: Desk edge, 0.75" - 1.75"
- Conforms and tested to UL 962A and UL 1310 standards
- Tamper-resistant (TR) AC outlets
- Integrated circuit breaker

Specifications

Input: 125VAC, 60Hz, 15A max
 Output:
 AC Outlets (2): 120VAC, 60HZ, 15A max
 Single port use:
 USB-A: 5V3A, 9V2.A, 12V1.5, 18W max
 USB-C1: 5V/3A, 9V3A, 12V3A, 15V3A, 20V3.25A;
 PPS (3.3-11V4.05A, 3.3-16V3A, 65W max);
 PD3.0, APPLE2.4A, DCP1.5A, QC2.0/3.0, AFC
 USB-C2: 5V3A, 9V2.22A, 12V1.67A, 20W max
 Multi port use:
 USB-C1 + USB-C2: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 max 20W (5V3A, 9V2.22A, 12V1.67A)
 USB-C1 + USB-A: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-A max 18W (5V3A, 9V2.A, 12V1.5, 18W max)
 USB-C2 + USB-A: Both share 15W
 USB-C1 + USB-C2 + USB-A: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 & USB-A share 15W

Dimensions

Product: 7.1" x 3.3" x 2.3"
 Cord Length: 6'


Part Numbers

PWR-ACC-__



WIRELESS SURFACE POWER MODULE

Finishes



Features

- 2 power receptacles
- 1 USB-A charger port
- 2 USB-C charger ports
- Can charge laptop up to 65 Watts
- Fast Qi certified wireless charging
- Mount: Desk edge, 0.75" - 1.75"
- Conforms and tested to UL 962A and UL 1310 standards
- Tamper-resistant (TR) AC outlets
- Integrated circuit breaker

Specifications

Input: 125VAC, 60Hz, 15A max
 Output:
 AC Outlets (2): 120VAC, 60HZ, 15A max
 Single port use:
 USB-A: 5V3A, 9V2.A, 12V1.5, 18W max
 USB-C1: 5V/3A, 9V3A, 12V3A, 15V3A, 20V3.25A; PPS (3.3-11V4.05A, 3.3-16V3A, 65W max), PD3.0, APPLE2.4A, DCP1.5A, QC2.0/3.0, AFC
 USB-C2: 5V3A, 9V2.22A, 12V1.67A, 20W max
 Multi port use:
 USB-C1 + USB-C2: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 max 20W (5V3A, 9V2.22A, 12V1.67A);
 USB-C1 + USB-A : USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-A max 18W (5V3A, 9V2.A, 12V1.5, 18W max)
 USB-C2 + USB-A : Both share 15W
 USB-C1 + USB-C2 + USB-A : USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 & USB-A share 15W;
 Wireless Charging: Qi 5W, 7.5W, 10W, 15W (auto detection);

Dimensions

Product: 7.1" x 3.3" x 2.4"
 Cord Length: 6'

Part Numbers

PWR-ACC-WRLS-__



POWER STRIP

Finishes

- White
WH
- Black
BK

Features

- 6 power receptacles
- Conforms and tested to UL 962A and UL 498 standards
- Tamper-resistant (TR) AC outlets
- Integrated circuit breaker

Specifications

- Input: 125VAC, 60Hz, 15A max
- Output:
- AC Outlets (6): 120VAC, 60HZ, 15A max

Dimensions

- Product: 14.6" x 2.4" x 1.5"
- Cord Length: 6'

Part Numbers

PWR-STRP-__



POWER STRIP WITH HARDWIRED STANDARD SURFACE POWER MODULE

Finishes

- White
WH
- Black
BK

Features

- Power Strip: 6 power receptacles
- Power Module: 2 power receptacles
 - 1 USB-A charger port
 - 2 USB-C charger ports
 - Can charge laptop up to 65 Watts

- Conforms and tested to UL 962A, UL 1310, and UL 498 standards
- Tamper-resistant (TR) AC outlets
- Integrated circuit breaker

Specifications

- Input: 125VAC, 60Hz, 15A max
- Output, Power Strip:
- AC Outlets (6): 120VAC, 60HZ, 12A max
- Output, Surface Mounted Power Module:
- AC Outlets (2): 120VAC, 60HZ, 15A max
- USB:
 - Single Port Use
 - USB-A: 5V3A, 9V2.A, 12V1.5, 18W max
 - USB-C1: 5V/3A, 9V3A, 12V3A, 15V3A, 20V3.25A; PPS (3.3-11V4.05A, 3.3-16V3A, 65W max), PD3.0, APPLE2.4A, DCP1.5A, QC2.0/3.0, AFC
 - USB-C2: 5V3A, 9V2.22A, 12V1.67A, 20W max
 - Multi Port Use
 - USB-C1 + USB-C2: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 max 20W (5V3A, 9V2.22A, 12V1.67A)
 - USB-C1 + USB-A: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-A max 18W (5V3A, 9V2.A, 12V1.5, 18W max)
 - USB-C2 + USB-A: Both share 15W
 - USB-C1 + USB-C2 + USB-A : USB-C1 max 45W (5V3A, 9V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 & USB-A share 15W

Dimensions

- Surface Unit: 7.1" x 3.3" x 2.4"
- Power Strip: 14.6" x 2.4" x 1.5"
- Cord Length:
 - Input: 6'
 - Between Units: 3'

Part Numbers

PWR-ACC-STRP-__