



FUSION SERIES

MEDICAL CARTS



HAT
COLLECTIVE™
HEALTHCARE

A LIGHTWEIGHT POWERHOUSE.

The Fusion Series is designed for effortless mobility. From the slim silhouette to the compact and lightweight base design, the series is ideal for maneuvering in space constrained environments.



FEATURES

- **Ergonomic:** Various monitor mounts available that offer tilt, swivel and pivot adjustments.
- **Protected:** Simoguard™ antimicrobial protection built in to inhibit the growth of bacteria and mold.
- **Expansive:** Ample, desktop workspace. An extended worksurface is also available.
- **Smart:** Desktop overlay indicates the power system's battery run-time and charge time in hours/minutes (powered carts).
- **Integrated:** Built-in handles allow easy maneuvering and control.
- **Retractable:** Keyboard tray retracts when not in use and offers a sliding mouse tray for left or right-handed compatibility.
- **Adjustable:** Single hand height adjustment for user comfort when standing or sitting.
- **Easy:** Ships fully assembled.

SPECIFICATIONS

Finishes

	Tidal Blue		Sandstone
	Aqua Wave		Granite
	Lavender Mist		Onyx
	Pink for the Cure		Evergreen (Special Order)
	Apple		Sunburst (Special Order)
	Orange Blast		

Dimensions

Base:
15" W (front) x 19" W (back) x 18" D
Casters: 5" single wheels
(2 non-locking, 1 locking and
1 steering caster w/lock)
Worksurface Construction:
Antimicrobial, high-density
polypropylene & polyethylene
Cart Sleeve & Base: Styrene &
injected molded plastic

Mobile Power Options

See page 4

WARRANTY

5 Years (excluding accessories & power components)

FUSION CONFIGURATIONS



FUSION HYBRID
Worksurface Area: 23" W x 12.5" D
Worksurface Height: 37" - 48.25"
Keyboard Tray Size: 20" W x 10" D
Keyboard Tray Height: 30" - 42"



FUSION THIN CLIENT
Worksurface Area: 20.75" W x 11.25" D
Worksurface Height: 34.25" - 45.75"
Keyboard Tray Size: 20" W x 10" D
Keyboard Tray Height: 30" - 42"



FUSION LAPTOP
Worksurface Area: 23" W x 12.5" D
Worksurface Height: 36.75" - 48"
Keyboard Tray Size: 20" W x 10" D
Keyboard Tray Height: 30" - 42"



FUSION IPATH
Worksurface Area: 22" W x 16" D
Worksurface Height: 34.5" - 45.5"



MEDICAL CART POWER SYSTEMS

	Laptop Computer		Hybrid / Thin Client Computer w/Monitor		All-in-One Computer	
	Option 1	Option 2	Option 1	Option 2	Option 1	Option 2
Power System Model	Stealth Power Basic 450W / 22.2 Ah	Stealth Power 450W / 44.4 Ah	Stealth Power 450W / 44.4 Ah	Stealth Power Plus 450W / 66.6 Ah	Stealth Power 450W / 66. Ah	Stealth Power Plus 450W / 66.6 Ah
Battery Chemistry	LiFePO4 Lithium Iron Phosphate	LiFePO4 Lithium Iron Phosphate	LiFePO4 Lithium Iron Phosphate	LiFePO4 Lithium Iron Phosphate	LiFePO4 Lithium Iron Phosphate	LiFePO4 Lithium Iron Phosphate
Battery Capacity	12.8 Volt / 44.4 Ah	12.8 Volt / 44.4 Ah	12.8 Volt / 44.4 Ah	12.8 Volt / 66.6 Ah	12.8 Volt / 44.4 Ah	12.8 Volt / 66.6 Ah
Battery Run Time	8 Hours @ 35 Watts 4.5 Hours @ 65 Watts	25 Hours @ 35 Watts 13 Hours @ 65 Watts	13 Hours @ 65 Watts 10 Hours @ 90 Watts 8 Hours @ 110 Watts	20 Hours @ 65 Watts 15 Hours @ 90 Watts 12 Hours @ 110 Watts	13 Hours @ 65 Watts 10 Hours @ 90 Watts 8 Hours @ 110 Watts	20 Hours @ 65 Watts 15 Hours @ 90 Watts 12 Hours @ 110 Watts
Recharge Time	≤ 2 Hours	≤ 2 Hours	≤ 2 Hours	2.25 Hours	≤ 2 Hours	2.25 Hours
Battery Life	2500 - 3000 Cycles	2500 - 3000 Cycles	2500 - 3000 Cycles	2500 - 3000 Cycles	2500 - 3000 Cycles	2500 - 3000 Cycles
Technology / Flexibility	Built-in AC & DC Output AC Plug w/ 3 Outlets 3 DC Outputs: 5v, 12v & 19.5v	Built-in AC & DC Output AC Plug w/ 3 Outlets 3 DC Outputs: 5v, 12v & 19.5v	Built-in AC & DC Output AC Plug w/ 3 Outlets 3 DC Outputs: 5v, 12v & 19.5v	Built-in AC & DC Output AC Plug w/ 3 Outlets 3 DC Outputs: 5v, 12v & 19.5v	Built-in AC & DC Output AC Plug w/ 3 Outlets 3 DC Outputs: 5v, 12v & 19.5v	Built-in AC & DC Output AC Plug w/ 3 Outlets 3 DC Outputs: 5v, 12v & 19.5v
Total Power Available	450 Watts	450 Watts	450 Watts	450 Watts	450 Watts	450 Watts
Safety Compliance	UL 60601 3rd Edition	UL 60601 3rd Edition	UL 60601 3rd Edition	UL 60601 3rd Edition	UL 60601 3rd Edition	UL 60601 3rd Edition

